



PRODUCT INDEX OEM and Retail

- 2,3 Intelli-Power 9200 Series Converter/Chargers
- 4,5 Intelli-Power 9100 Series Converter/Chargers
- 6 Intelli-Power 4600 Series Converter/Chargers
- 7 Intelli-Power 4000 Series Converter/Chargers
- 8 Intelli-Power 4500 Series Converter/Chargers
- 9 Intelli-Power 4300 Series Converter/Chargers
- 10 5000 Series AC/DC 120VAC Power Distribution Panel
- 11 5500 Series AC/DC 240VAC Power Distribution Panel
- 12 6000 Series DC Power Distribution Panel
- 13 5100 & 5200 Series Automatic Transfer Switches
- 14, 15 Intelli-Power Marine 2100 Series Electronic Converter/Chargers
- 16 220 Series Fluorescent Lights for RV & Marine
- 17 790 Series Ceiling Lights
- 18 780 Series Ceiling Lights
- 19 770 Series Ceiling Lights
- 20 760 Series Ceiling Lights
- 21 750 Series Ceiling Lights
- 22 12 Volt Convenience Lights and Reading Lights
- 23 Lighting Accessories

Product specifications are subject to change without notice.

INTELI-POWER 9200 SERIES

RV Converter/Chargers

with built-in CHARGE WIZARD



Built-in CHARGE WIZARD constantly monitors voltage status and automatically manages your battery.

INTELI-POWER 9200 SERIES models can recharge the battery to 90% in 2-3 hours using our patented CHARGE WIZARD technology.

The built-in CHARGE WIZARD automatically selects one of four operating modes: BOOST, NORMAL, STORAGE, DESULFATION.

BOOST Mode 14.4 Volts - Rapidly brings RV battery up to 90% of full charge.

NORMAL Mode 13.6 Volts - Safely completes the charge.

STORAGE Mode 13.2 Volts - Maintains charge with minimal gassing or water loss.

DESULFATION Mode 14.4 Volts - Every 21 hours for a period of 15 minutes to prevent battery stratification.

Covered by one or more of the following U.S. Patents: 5,600,550, 5,687,066, 5,982,643, 6,184,649. Additional patents pending.




All Models Available for Lead-Acid or Gel-Cell Batteries

Engineered for power-hungry applications

Standard features on all models:

- **Built-in CHARGE WIZARD constantly monitors voltage status and automatically manages your battery.**
- Built-in accessory port for optional Pendant (standard on retail units) to **monitor CHARGE WIZARD operating modes.**
- Reverse battery protection **protects converter from damage resulting from improper (reverse) battery lead connection.**
- These solid-state converter/chargers deliver filtered DC power to all 12 Volt lighting and appliance circuits **providing safe and reliable service.**
- Electronic current limiting automatically reduces output voltage when maximum capacity is reached. **Protects your investment and offers peace of mind.**
- Low line voltage protection automatically shuts converter down if input voltage is insufficient and **protects your appliances from damaging low voltage irregularities.**
- Variable speed intelligent cooling fan automatically monitors converter temperature and activates fan at speed required. **Very slow quiet speeds are used when demand is low such as during sleeping hours.**
- High voltage protection **protects converter from spikes or surge of voltage over 135V.**
- Automatic thermal protection reduces converter output to safe levels when unit temperature exceeds pre-set limits and **protects converter from damage due to excessive heat.**
- 2 year limited warranty.



Retail Display Package – Colorful graphics grab attention. Product features and benefits are displayed on all panels.

Retail Model PD9280V

OEM Model PD9280

Input: 105-130 VAC,
50/60 Hz, 1300 Watts

Output: 13.6 VDC, 80 Amp

Dimensions: 3.6" H x 11.5" L x 9" W

Weight: 7.5 lbs.

Uses a 20 AMP cord*



*Removal or alteration of converter 20 AMP power cord will void warranty.



80
AMP

Retail Model PD9270V

OEM Model PD9270

Input: 105-130 VAC,
50/60 Hz, 1250 Watts

Output: 13.6 VDC, 70 Amp

Dimensions: 3.6" H x 8" L x 9" W

Weight: 5.8 lbs.



70
AMP

Retail Model PD9260CV

OEM Model PD9260C

Input: 105-130 VAC,
50/60 Hz, 1000 Watts

Output: 13.6 VDC, 60 Amp

Dimensions: 3.6" H x 8" L x 9" W

Weight: 5.8 lbs.



60
AMP

Retail Model PD9245CV

OEM Model PD9245C

Input: 105-130 VAC,
50/60 Hz, 725 Watts

Output: 13.6 VDC, 45 Amp

Dimensions: 4.5" H x 8.25" L x 7.25" W

Weight: 4.5 lbs.



45
AMP

Retail Model Pendant PD92201

(Optional on OEM units)

Plugs into the accessory port to show charger/converter status and allows for manual mode selection. The Pendant is included with all retail models.

U.S. Patent 6,184,649

Retail Display Package

– Colorful graphics grab attention and the large window shows the product. The package is designed for pegboard or slatwall display.

