

Solar Products ►

2088 Series Delivery Pumps - AUTOMATIC DEMAND 12VDC

Features:



Premium Pump w/ cooling fins

Standard

- Self priming up to 12 feet
- Can run dry without damage
- Optional motor cooling fins
- One way check valve prevents reverse flow
- Available for 12 VDC, 24 VDC, and 115 VAC
- Automatic operation with pressure demand switch

SHURflo 2088 Series diaphragm pumps deliver reliable performance in high flow, moderate pressure applications. They are used in a variety of transfer and dispense-on demand applications where flow to 3.6 GPM is required. For added reliability the Twist-on Strainer can be used on the 2088 inlet port. Install optional 4" or 5" heatsink for heavy duty applications where extra cooling is required.

Model	Description
2088-443-144	Standard Demand Pump 3.5 GPM open flow, Santoprene® valves, Santoprene® diaphragm, 45 PSI Demand Switch, 1/2" MSPT ports, Poly Housing
2088-514-145	Premium Pump w/Fin Cooled Motor 3.6 open flow, Santoprene® valves, Santoprene® diaphragm, 45 PSI Demand Switch, 1/2" MSPT ports. Poly Housing
2088-414-534	Premium Pump w/ Splash-Proof ShurCoted Motor 3.6 GPM open flow, Santoprene® valves Santoprene® diaphragm, 45 PSI Demand Switch, 1/2" MSPT ports, Poly Housing
2088-474-144	Standard Demand Pump 3.0 GPM open flow, Santoprene® valves, Santoprene® diaphragm, 45 PSI Demand Switch, 1/2" MSPT ports, Poly Housing
2088-574-534	Premium Pump w/Sealed Motor 3.6 GPM open flow, Santoprene® valves, Santoprene® diaphragm, 45 PSI Demand Switch, 1/2" MSPT* ports, Poly Housing
2088-594-154	Standard Demand Pump 3.3 GPM open flow, Santoprene® valves, Santoprene® diaphragm, 45 PSI Demand Switch, 1/2" MSPT* ports, Poly Housing
2088-514-144	Standard Demand Pump 3.8 GPM open flow, Santoprene® valves, Santoprene® diaphragm, 45 PSI Demand Switch, 1/2" MSPT* ports, Poly Housing

Products
What's New
Events Calendar
Dealers

contact us
site map
home

[▲ top of page](#)

