



TS4-A-O

PV Module Advanced Add-On/Retrofit

The TS4-A-O (Optimization) is the advanced add-on/retrofit optimization solution that brings smart module functionality to standard PV modules for higher reliability. Improve energy efficiency by upgrading underperforming PV systems or adding smart features to new installations.

The TS4-A-O with UHD-Core technology and expanded specifications supports PV modules up to 500W.

Included Features



Module-level **optimization** for increased energy yield and greater design flexibility



Enhanced **safety** for NEC 690.12 rapid shutdown compliance



Module-level **monitoring** for energy production tracking and system management

Easy Installation

Snap to standard module frame or remove brackets for rack mounting


Smart Commissioning

Configure and commission with your Android or iOS mobile device



TS4-A-O SPECIFICATIONS

Environmental	
Operating Temperature Range	-40°C to +85°C (-40°F to +158°F)
Outdoor Rating	IP68, NEMA 3R
Mechanical	
Dimensions	138.4mm x 139.7mm x 22.9mm
Weight	490g
Electrical	
Voltage Range	16 - 90V
Maximum Continuous Input Current (IMAX)	12A
Maximum Power	500W
Output Cable Length	1m (standard)
Connectors	MC4 compatible (standard)
Communication Type	Wireless
Rapid Shutdown UL Listed (NEC 2014 & 2017 690.12)	Yes



Cloud Connect Advanced (CCA) and TAP (Gateway) required for rapid shutdown with TS4-A-O.

ORDERING INFORMATION

Standard	
451-00257-00	1000V UL / TÜV, 1m cable, MC4 compatible
Options	
451-00252-12	1000V UL / TÜV, 1m cable, MC4
451-00257-12	1000V UL / TÜV, 1.2m cable, MC4 compatible
451-00252-32	1000V UL / TÜV, 1.2m cable, MC4
451-00261-12	1500V UL / TÜV, 1m cable, EVO2
451-00261-32	1500V UL / TÜV, 1.2m cable, EVO2

For sales info:

sales@tigoenergy.com or 1.408.402.0802

For product info:

Visit tigoenergy.com/products

For technical info:

Visit support.tigoenergy.com

For additional info and product selection assistance, use Tigo's online design tool at tigoenergy.com/design











